

Kruz

“Tub” Type

ENGINEERED FOR RIGOROUS USE AND LONGEVITY



TERMINATOR STEEL DUMP TRAILER

The workhorse since 1993, Terminator trailers are built for maximum capacity and performance. Kruz steel dump trailers are revolutionary in design with HARDOX rounded sides and a flat floor. HARDOX steel is quenched for a smoother surface, light-weight and excellent impact resistance. The flat interior bulkhead slopes for easy “no hand” dumping.

Kruz steel dump trailers are available in frame, frameless and semi-frameless designs at dealers from coast to coast.

**FRAME
SEMIFRAME
FRAMELESS**

Kruz

High Strength, Heavy-Duty HARDOX STEEL



PHOTOS MAY SHOW OPTIONAL EQUIPMENT.
PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Chassis Specifications

Standard Frame:	22'-26' 16" I-Beam 28'-39' 18" I-Beam
Frame Crossmembers:	1/4"
Hoist Cylinder:	Commercial 8" 4 or 5 Stage
Standard Suspension:	Watson 44K S/P
Standard Axles:	5/8" Wall, 25K Meritor
Standard Wheel:	22.5 Hub Piloted Steel, White
Hubs:	Duralite Steel
Brakes:	Auto Slack, 30/30, WABCO 4S-2M
Drums:	Centrifuse
Standard Tires:	11R22.5 14 Ply
Brake Chamber Protector:	Standard
Standard Landing Gear:	Stiff Legs

Body Specifications

Standard Floor:	3/16" HARDOX 450
Platform Rails:	1/4" x 4" x 8" Rect Tubing
Standard Crossmember:	1/4" x 3" x 3" Tubing on 18" Centers
Rear Crossmember:	1/4" Plate Formed
Suspension Plate:	3/4" Full Width
Saddle Mount:	3"
Standard Rear Hinge:	Cast Steel
Asphalt Hinge:	Optional
Rear Hinge Pin:	1 15/16" Stress Proof
Main Draftarm "SFS":	1/4" x 7" Tapered T-1
Main Draftarm "FFS":	1/4" x 3" x 5" Rect Tube
Secondary Draftarm "SFS":	3/16" x 2" x 4" Rect Tube
Kingpin Plate:	3/8", 1 15/16" Draftarm Shaft
Standard Sides:	3/16" HARDOX 450
Side Heights:	55" / 60" / 66" / 72"
Standard Fenders:	Full Length and Front
Top Rail:	3/16" x 4" x 6" Rect Tubing
Standard Rear Post:	1/4" x 15" Formed
Standard Bulkhead:	3/16" HARDOX 450
Bulkhead Heights:	55" / 60" / 66" / 72"
Inside Doghouse:	1/4" Formed
Outside Doghouse:	3/16"
Upper Cylinder Plate:	3/8"
Upper Cylinder Mount Bracket:	1"
Standard Tailgate:	3/16" HARDOX 450
Tailgate Heights:	55" / 60" / 66" / 72"
Standard Tailgate Style:	Top Swing Side Swing Two Way (Dump and Side)
Optional Tailgate Style:	High Lift/ Dual Action
Standard Tailgate Bracing:	3/16" x 4" x 3" Tubing / Vertical, 3 Panel
Tailgate Dirt Shedder:	3/16"
Tailgate Latch Pin:	1 1/4"
Tailgate Latch Base:	3/8"
Tailgate Latch Hook:	3/4"
Tailgate Recessed Hinge:	3/8"
Standard Spreader Pan:	Apron (Weld On) 1/4" x 12" Reinforced with Push
Standard Ladder:	Rung Ladder on Bulkhead with Steps on inside left hand
Mudflaps:	Kruz Anti-Sail
Electrical:	7-Way, 2-Sided Markers, 4STT, Sealed Beam
LED Lights:	Standard
Cylinder Hose:	22" - 24" 108" with Wing Disconnect 26" - 39" 140" with Wing Disconnect

KRUZ INC
1201W CULVER RD * KNOX, IN 46534
PH: 574-772-6673 * FX: 574-772-3298
WWW.KRUZINC.COM