

# **Kruz**

# **ROUND BOTTOM**

ENGINEERED FOR RIGOROUS USE AND LONGEVITY



## ***TERMINATOR 'RB' STEEL DUMP TRAILER***

The workhorse since 1993, Terminator and Terminator RB trailers are built for maximum capacity and performance. Kruz steel dump trailers are revolutionary in design with HARDOX rounded sides and a flat floor. HARDOX steel is quenched for a smoother surface, light-weight and excellent impact resistance. The flat interior bulkhead slopes for easy “no hand” dumping.

Kruz steel dump trailers are available in frame, frameless and semi-frameless designs at dealers from coast to coast.

**FRAME  
SEMIFRAME  
FRAMELESS**

# **Kruz**

# High Strength, Heavy-Duty HARDOX STEEL

## Chassis Specifications

<b>Standard Frame:</b>	22'-26' 16" I-Beam / 28'-39' 18" I-Beam
<b>Frame Crossmembers:</b>	3/16" A572 Formed
<b>Suspension Crossmembers:</b>	1/4" wall 6" x 4" Structural Tubing
<b>Hoist Cylinder:</b>	Commercial or Custom 8" 4 or 5 Stage
<b>Standard Suspension:</b>	Watson 44K S/P
<b>Standard Axles:</b>	5/8" Wall, 25K Meritor
<b>Standard Wheel:</b>	22.5 Hub Piloted Steel, White
<b>Hubs:</b>	Duralite Steel
<b>Brakes:</b>	Auto Slack, 30/30, WABCO 4S-2M
<b>Drums:</b>	Centrifuse
<b>Standard Tires:</b>	11R22.5 16 Ply
<b>Brake Chamber Protector:</b>	Standard
<b>Standard Landing Gear:</b>	Stiff Legs

## Body Specifications

<b>Standard Floor:</b>	3/16" HARDOX 450
<b>Platform Rails:</b>	1/4" x 4" x 8" Rect Tubing
<b>Suspension Plate:</b>	3/4" Full Width
<b>Saddle Mount:</b>	3"
<b>Standard Rear Hinge:</b>	Fabricated Steel
<b>Asphalt Hinge:</b>	Optional
<b>Rear Hinge Pin:</b>	1 15/16" Stress Proof
<b>Main Draftarm "SFS":</b>	1/4" x 7" Tapered T-1
<b>Main Draftarm "FFS":</b>	1/4" x 3" x 5" Rect Tube
<b>Secondary Draftarm "SFS":</b>	3/16" x 2" x 4" Rect Tube
<b>Kingpin Plate:</b>	3/8", 1 15/16" Draftarm Shaft
<b>Standard Sides:</b>	3/16" HARDOX 450
<b>Side Heights:</b>	55" / 60" / 66" / 72"
<b>Standard Fenders:</b>	Full Length and Front
<b>Top Rail:</b>	3/16" x 4" x 6" Rect Tubing
<b>Standard Rear Post:</b>	1/4" x 15" Formed
<b>Standard Bulkhead:</b>	3/16" HARDOX 450
<b>Bulkhead Heights:</b>	55" / 60" / 66" / 72"
<b>Inside Doghouse:</b>	1/4" Formed
<b>Outside Doghouse:</b>	3/16"
<b>Upper Cylinder Plate:</b>	3/8" Formed
<b>Upper Cylinder Mount Bracket:</b>	1"
<b>Standard Tailgate:</b>	3/16" HARDOX 450
<b>Tailgate Heights:</b>	55" / 60" / 66" / 72"
<b>Standard Tailgate Style:</b>	Top Swing
<b>Optional Tailgate Style:</b>	Side Swing Two Way (Dump and Side) High Lift/ Dual Action
<b>Standard Tailgate Bracing:</b>	3/16" x 4" x 3" Tubing / Vertical, 3 Panel
<b>Tailgate Dirt Shedder:</b>	3/16"
<b>Tailgate Latch Pin:</b>	1 1/4"
<b>Tailgate Latch Base:</b>	3/8"
<b>Tailgate Latch Hook:</b>	3/4"
<b>Tailgate Recessed Hinge:</b>	3/8"
<b>Standard Spreader Pan:</b>	Apron (Weld On) 1/4" x 12" Reinforced with Push
<b>Standard Ladder:</b>	Rung Ladder on Bulkhead with Steps on inside left hand
<b>Mudflaps:</b>	Kruz Logo Rubber Anti-Sail
<b>Electrical:</b>	7-Way, 2-Sided Markers, 4STT, Sealed Beam
<b>LED Lights:</b>	Standard
<b>Cylinder Hose:</b>	22' - 24' 108" with Wing Disconnect 26' - 39' 140" with Wing Disconnect



PHOTOS MAY SHOW OPTIONAL EQUIPMENT.  
PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

**KRUZ INC**  
1201W CULVER RD \* KNOX, IN 46534  
PH: 574-772-6673 \* FX: 574-772-3298  
WWW.KRUZINC.COM